



The Ultimate Lubricant

636

DESCRIPTION:

Omega 636 is a universal, multi-purpose lubricant designed for maximum surface penetration power, superior water displacement capability and engineered for a wide variety of applications in the workshop for maintenance.

SURFACE PROTECTION:

Omega 636 offers an unprecedented standard of protection for metal surfaces against corrosion caused by oxidation. Not only does this product penetrate the metal surface, it also leaves a thin protective surface film that resists oxidation, rust and corrosion.

RUST PROTECTION:

Omega 636 is so versatile that can be used as a rust protection before applying other heavy-duty anti-corrosion coatings or treatments (excluding paints or primers, since Omega 636's oiliness will affect surface adhesion).

LONG LASTING:

Unlike ordinary penetrating oils and water displacers that easily become unstable, Omega 636 retains its stability through specially-formulated thermal conductors, myoثرitic ions and an insulated, built-in system of gyrogistics. These combine together to ensure long-lasting protection.

UNYIELDING LUBRICITY:

Omega 636's viscous lubricating film greatly reduces friction, heat and wear. Pressure-activated EP additives effortlessly overcome lubricating emergencies such as when sudden and/or excessive pressure threatens to rupture the lubricating film to cause disastrous metal-to-metal contact.

TYPICAL DATA:

TEST	ASTM TEST METHOD	TEST RESULT
Appearance	Visual	Transparent Green
Density, Kg/L @ 15°C	D-1298	0.843
Viscosity, cSt @ 40°C	D-445	9.8
Flash Point, COC, °C(°F)	D-92	67(152.6)
Pour Point, °C (°F)	D-97	-17(1.4)
Film Thickness @25°C(76°F)	Proprietary	0.2 mil
Coverage @25°C (76°F) sq. ft/U.S. gallon	Proprietary	3000
Water Displacement Characteristics	Proprietary	Pass
Rust-Preventing Characteristics -		
Cast Iron Chips, RH100%, 72 hrs.	Proprietary	Pass

APPLICATION:

Omega 636 can be used in all medium to small size machinery and equipment as a rust inhibitor, surface protector, fingerprint and perspiration suppressant and active water displacer. It can also be used as a light-duty lubricant during deep penetration applications. Unlike cheap kerosene/light oil products that easily wash off, Omega 636 stubbornly adheres. Apply in a sprayer, as a drip, with a brush or as a dip.

SAFETY DATA SHEET



Product name: Omega 636
Supersedes date: 2021-05-20
Product No.:

Page: 1/12
Last revised date: 2023-01-20
SDS-ID: GB-EN/9.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name: Omega 636
UFI: JMEJ-V7FD-NSHH-92M1
Container size: 5 l, 20 l, 205 l

1.2. Relevant identified uses of the substance or mixture and uses advised against

Application: Multipurpose oil. (Lubricant., Rust inhibitor.)

1.3. Details of the supplier of the safety data sheet

Supplier: Sovereign Lubricants (UK), Ltd
Crowtrees Lane - Rastrick - West Yorkshire - HD6 3LZ
Tel:01484 718674
Fax:01484 400164
enquiries@sovereign-omega.co.uk
www.sovereign-omega.co.uk

Manufacturer: ITW PP & F Korea Limited
13th Fl., Unit B, PAX Tower
609 Eonju-ro, Gangnam-Gu
Seoul, Korea 06108
Tel:+82-2-2088-3560
Fax:+82-2-513-3567
magna@magnagroup.com
www.magnagroup.com

Further information can be obtained from: magna@magnagroup.com

1.4. Emergency telephone number

Emergency telephone: NHS: 111

SAFETY DATA SHEET

Product name: Omega 636 Page: 2/12
Supersedes date: 2021-05-20 Last revised date: 2023-01-20
Product No.: SDS-ID: GB-EN/9.0

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP: The product is classified: Skin Irrit. 2;H315 - Asp. Tox. 1;H304

2.2. Label elements



Danger

Contains: Naphtha (petroleum), hydrotreated heavy

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

P260 Do not breathe vapour/spray.

P280 Wear protective clothing and gloves, and eye protection.

P262 Do not get in eyes, on skin, or on clothing.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P501 Dispose of contents/container as hazardous waste.

Contains Pine oil and Methyl salicylate. May produce an allergic reaction.
Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

PBT/vPvB: This product does not contain any PBT or vPvB substances.

Other: The product contains a sensitising substance which may provoke an allergic reaction among sensitive individuals.
The product is combustible, but not flammable. Prolonged or repeated contact with skin may cause redness, itching, irritation, eczema, skin cracking and oil acne. The harmful effects may increase in used oil.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

SAFETY DATA SHEET

Product name:	Omega 636	Page:	3/12
Supersedes date:	2021-05-20	Last revised date:	2023-01-20
Product No.:		SDS-ID:	GB-EN/9.0

The product contains: mineral oil, organic solvents and additives.
 Only classified substances above threshold limits or substances with an exposure limit are shown.

CLP:

<u>%:</u>	<u>CAS-No.:</u>	<u>EC No.:</u>	<u>REACH Reg. No:</u>	<u>Chemical name:</u>	<u>Hazard classification:</u>	<u>Notes:</u>
30-60	64742-48-9	265-150-3	01-2119486659-16-0041	Naphtha (petroleum), hydrotreated heavy	Asp. Tox. 1;H304 EUH066	P
30-60	64742-54-7	265-157-1	01-2119484627-25-0099	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil-unspecified	-	L
1-5	111-76-2	203-905-0	-	2-Butoxyethanol	Acute Tox. 4*;H332 Acute Tox. 4;H302 Eye Irrit. 2;H319 Skin Irrit. 2;H315	
1-5	8002-09-3	616-792-1	-	Pine oil	Flam. Liq. 3;H226 Skin Irrit. 2;H315 Skin Sens. 1;H317 Asp. Tox. 1;H304 Aquatic Chronic 2;H411	
0.1-<1	119-36-8	204-317-7	-	Methyl salicylate	Repr. 2;H361d Acute Tox. 4;H302 Skin Sens. 1B;H317 Aquatic Chronic 3;H412	

<u>Chemical name:</u>	<u>SCL</u>	<u>M (ac)</u>	<u>M (chr)</u>	<u>ATE(o)</u> <u>(mg/kg</u> <u>bw)</u>	<u>ATE(d)</u> <u>(mg/kg</u> <u>bw)</u>	<u>ATE(i)</u> <u>(vapour,</u> <u>mg/L)</u>
Naphtha (petroleum), hydrotreated heavy		-	-	-	-	-
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil-unspecified		-	-	-	-	-
2-Butoxyethanol	-	-	-	1200	-	-
Pine oil		-	-	-	-	-
Methyl salicylate	-	-	-	890	-	-

Notes:

P: benzene < 0,1% (w/w)
 L: DMSO < 3% (IP 346)

References:

The full text for all hazard statements is displayed in section 16.

SAFETY DATA SHEET

Product name:	Omega 636	Page:	4/12
Supersedes date:	2021-05-20	Last revised date:	2023-01-20
Product No.:		SDS-ID:	GB-EN/9.0

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation: Move into fresh air and keep at rest. In case of persistent throat irritation or coughing: Seek medical attention and bring these instructions.

Skin contact: Remove contaminated clothing immediately and rinse skin with rinsing cream. After this, apply a fatty cream. In case of rashes, wounds or other skin disorders: Seek medical attention and bring along these instructions.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Seek medical attention and bring along these instructions.

Ingestion: Immediately rinse mouth and drink 1-2 glasses of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Immediate transport to hospital. Bring along these instructions.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects: Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. Be aware that symptoms of lung oedema (shortness of breath) may develop up to 24 hours after exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Medical attention/treatments: Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.
Small fires: Extinguish with carbon dioxide or dry powder.
Larger fires: Extinguish with foam, carbon dioxide or dry powder.
Do not use water jet as an extinguisher, as this will spread the fire.

Cool containers exposed to heat with water spray and remove container, if no risk is involved.

5.2. Special hazards arising from the substance or mixture

Specific hazards: During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Protective equipment for fire-fighters: Selection of respiratory protection for fire fighting: follow the general fire precautions indicated in the workplace.

SAFETY DATA SHEET

Product name:	Omega 636	Page:	5/12
Supersedes date:	2021-05-20	Last revised date:	2023-01-20
Product No.:		SDS-ID:	GB-EN/9.0

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Avoid inhalation of vapours/oil mist and contact with skin and eyes. Follow precautions for safe handling described in this safety data sheet.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up: Absorb spillage with non-combustible, absorbent material. Clean contaminated area with oil-removing material.

6.4. Reference to other sections

References: For personal protection, see section 8.
For waste disposal, see section 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Safe handling advice: Observe good chemical hygiene practices. Avoid inhalation of vapours/oil mist and contact with skin and eyes. Avoid prolonged and repeated contact with oil, particularly used oil. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags moistened with oil into pockets.

Technical measures: Work practice should minimise contact.
Use work methods which minimise oil mist production.

Technical precautions: Mechanical ventilation may be required.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures for safe storage: Follow rules for flammable liquids. Large amounts and inventory should be stored in accordance with national regulation on storage of flammable liquids.

Storage conditions: Store in tightly closed original container in a dry, cool and well-ventilated place.
Do not store near heat sources or expose to high temperatures.

7.3. Specific end use(s)

Specific use(s): Not relevant.

SAFETY DATA SHEET

Product name: Omega 636 Page: 6/12
Supersedes date: 2021-05-20 Last revised date: 2023-01-20
Product No.: SDS-ID: GB-EN/9.0

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits:

<u>CAS-No.:</u>	<u>Chemical name:</u>	<u>As:</u>	<u>Exposure limits:</u>		<u>Type:</u>	<u>Notes:</u>	<u>References:</u>
111-76-2	2-Butoxyethanol	-	25 ppm	123 mg/m ³	TWA	Sk	EH40
		-	50 ppm	246 mg/m ³	STEL	Sk; 15min	
-	Normal and branched chain alkanes >=C7 (excluding n-Heptane)	-		1200 mg/m ³	TWA	-	EH40

Notes:

Sk: Can be absorbed through skin.
EH40: EH40/2005.

8.2. Exposure controls

Engineering measures:

Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours and oil mist. Provide access to washing facilities incl. soap, skin cleanser and fatty cream.

Personal protection:

Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Respiratory equipment:

In case of inadequate ventilation or risk of inhalation of oil mist, suitable respiratory equipment with combination filter (type A2/P3) can be used.

Hand protection:

Wear protective gloves.
PVC gloves are recommended.
Thickness: >0.35 mm; Breakthrough time: >240 min.
The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

Eye protection:

Risk of contact: Wear goggles/face shield.

Skin protection:

Wear apron or protective clothing in case of splashes.

Hygiene measures:

Wash hands after handling. Wash contaminated clothing before reuse.

Environmental Exposure Controls:

Not available.

SAFETY DATA SHEET

Product name: Omega 636
Supersedes date: 2021-05-20
Product No.:

Page: 7/12
Last revised date: 2023-01-20
SDS-ID: GB-EN/9.0

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state: Oily. / green liquid
Odour: Solvent.
Odour threshold: Not available.
pH: Not available.
Melting point / freezing point: Not available.
Boiling point: Not available.
Flash point: > 67°C
Evaporation rate: Not available.
Flammability (solid, gas): Not relevant.
Explosive limits Not available.
Vapour pressure: Not available.
Vapour density: Not available.
Relative density: 0,84
Solubility: insoluble in water
Partition coefficient (n-octanol/water): Not available.
Auto-ignition temperature (°C): Not available.
Decomposition temperature (°C): Not available.
Viscosity: Kinematic viscosity: ~ 14 mm²/s
Explosive properties: Not available.
Oxidising properties: Not available.

9.2. Other information

Other data: Not available.

SAFETY DATA SHEET

Product name: Omega 636
Supersedes date: 2021-05-20
Product No.:

Page: 8/12
Last revised date: 2023-01-20
SDS-ID: GB-EN/9.0

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity: Not reactive.

10.2. Chemical stability

Stability: Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid Keep away from heat and direct sunlight.

10.5. Incompatible materials

Incompatible materials: Strong oxidising substances.

10.6. Hazardous decomposition products

Hazardous decomposition products: None in particular.

SAFETY DATA SHEET

Product name:	Omega 636	Page:	9/12
Supersedes date:	2021-05-20	Last revised date:	2023-01-20
Product No.:		SDS-ID:	GB-EN/9.0

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute Toxicity (Oral): Based on available data, the classification criteria are not met.

Acute Toxicity (Dermal): Based on available data, the classification criteria are not met.

Acute Toxicity (Inhalation): Based on available data, the classification criteria are not met.

Skin Corrosion/Irritation: Causes skin irritation.

Serious eye damage/irritation: Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive Toxicity: Based on available data, the classification criteria are not met.

STOT - Single exposure: Based on available data, the classification criteria are not met.

STOT - Repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: May be fatal if swallowed and enters airways.

Inhalation: Inhalation of oil mist or vapours formed during heating of the product will irritate the respiratory system and provoke coughing. The product contains organic solvents. In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea.

Skin contact: Degreasing. Repeated exposure may cause skin dryness or cracking. Prolonged or frequent contact may cause redness, itching, irritation, eczema, skin cracking and oil acne.
Contains butoxyethanol which may penetrate the skin.

Eye contact: Splashes may irritate.

Ingestion: Low order of acute toxicity, but aspiration following ingestion and vomiting may cause severe and potentially fatal chemical pneumonitis. May cause irritation. May be absorbed in the body and cause dizziness, nausea and vomiting.

Specific effects: The product contains small amounts of pine oil which may cause sensitisation. Prolonged or frequent inhalation of vapours in high concentrations may cause permanent damage to the nervous system, including the brain. Prolonged or repeated contact with used oil may cause serious skin diseases, such as dermatitis and skin cancer.

11.2. Information on other hazards

Endocrine disrupting properties: The product contains no substances identified as having endocrine disrupting properties in humans.

SAFETY DATA SHEET

Product name:	Omega 636	Page:	10/12
Supersedes date:	2021-05-20	Last revised date:	2023-01-20
Product No.:		SDS-ID:	GB-EN/9.0

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity: Oil spills are generally hazardous to the environment. The product contains a substance which may cause long term adverse effects in the environment.

12.2. Persistence and degradability

Degradability: The product is expected to be slowly biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available on bioaccumulation.

12.4. Mobility in soil

Mobility: The product is insoluble in water and will spread on the water surface.

12.5. Results of PBT and vPvB assessment

PBT/vPvB: This product does not contain any PBT or vPvB substances.

12.6. Endocrine disrupting properties

Endocrine disrupting properties: The product contains no substances identified as having endocrine disrupting properties in aquatic organisms.

12.7. Other adverse effects

Other adverse effects: The product contains volatile, organic compounds which have a photochemical ozone creation potential.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements. Waste is classified as hazardous waste.

Waste from residues: EWC-code: 13 02 05

Contaminated packaging: Dispose of contaminated packings as residue.

SAFETY DATA SHEET

Product name:	Omega 636	Page:	11/12
Supersedes date:	2021-05-20	Last revised date:	2023-01-20
Product No.:		SDS-ID:	GB-EN/9.0

SECTION 14: TRANSPORT INFORMATION

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/AND/RID).

14.1. UN number

UN-No: -

14.2. UN proper shipping name

Proper Shipping Name: -

14.3. Transport hazard class(es)

Class: -

14.4. Packing group

PG: -

14.5. Environmental hazards

Marine pollutant: -

Environmentally Hazardous substance: -

14.6. Special precautions for user

Special precautions: Not relevant.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk: Not relevant.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulation: UK Statutory Instruments, 2021 No. 904, CONSUMER PROTECTION ENVIRONMENTAL PROTECTION HEALTH AND SAFETY. The REACH etc. (Amendment) Regulations 2021.
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.
The Control of Substances Hazardous to Health Regulations 2002 (S.I. 2002 No. 2677) with amendments.
The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019 (SI 2019 No. 720), as amended.
EH40/2005, Workplace exposure limits 2005, with amendments.
The List of Wastes (England) (Amendment) Regulations 2005. (SI 2005 No. 895).

15.2. Chemical Safety Assessment

CSA status: No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

SAFETY DATA SHEET

Product name:	Omega 636	Page:	12/12
Supersedes date:	2021-05-20	Last revised date:	2023-01-20
Product No.:		SDS-ID:	GB-EN/9.0

Handling of used oils:

Protect health - avoid prolonged and repeated skin contact. Wash with soap and water. Protect the environment - do not pollute drains, water courses or the soil. Contact your local authority for any used oil disposal instructions.

The following sections contain revisions or new statements: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16.

Omega Manufacturing Division
13th floor, Unit B, PAX Tower, 609 Eonju-ro,
Gangnam-Gu, Seoul, Korea 06108
Tel : +82-2-2088-3560
Fax : +82-2-513-3567
Web site : www.magnagroup.com

The Omega Trade Mark is the property of ITW, Inc., and is used under license by ITW PP & F Korea Limited.

Abbreviations and acronyms

used in the safety data sheet: ATE(o) = Acute Toxicity Estimate, oral.
CSA= Chemical Safety Assessment.
PBT = Persistent, Bioaccumulative and Toxic.
vPvB = very Persistent and very Bioaccumulative.

Additional information: Classification according to Regulation (EC) No. 1272/2008: Calculation method.

Wording of H-statements:

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.

Made by DHI - Environment and Toxicology, Agern Allé 5, DK-2970 Hørsholm, Denmark.
www.dhigroup.com.
