



*The Ultimate Lubricant*

# 646

## **DESCRIPTION:**

Omega 646 is a fluid lubricant engineered exclusively for chains. It employs the high technology originally derived from the space age in which a super micronized solid lubricant – moly – is used to complement a high-grade, refined paraffinic oil in the lubrication of chains.

## **MULTITUDE OF MAINTENANCE**

### **USES:**

Omega 646 Fluid Lubricant for Chains is versatile. It promotes chain and parts life.

## **CHAIN LUBRICATION PROBLEMS:**

Conventional chain oils and greases lubricate by separating the load surfaces with a hydrodynamic film. This film cannot always be achieved in actual "in use" situations. Formation of this film is a function of many variables such as lubricant viscosity, surface speed and applied load. When speeds are too low, loads are too high, or there is an improper match of lubricant to viscosity to speed and load; and a plethora of other variables, metal-to-metal contact occurs to increase friction and subsequent excessive wear.

These conditions are not uncommon. They exist in normal operation such as during machinery start up, shutdown, during running-in of a replaced part and all through the operation of many heavily-loaded, slow-moving parts prevalent in chain driven machinery. A phenomena known as "chatter" or "stick slip" occurs and there is no lubrication between the chain and gear wheels!

## **RUNNING IN:**

Every new metal surface under a microscope is actually a series of valleys and peaks. When two such surfaces come into contact, only the peaks meet. Therefore these very small areas bear the entire load. These peaks "cold weld" together, then shear apart when movement occurs. Omega 646 -when applied to new parts before operating -can prevent actual contact between the peaks and prevent galling, scoring and catastrophic parts failure.

The moly in Omega 646 permits the surfaces to conform to each other by plastic deformation rather than potentially destructive welding and shearing. Omega 646 permits optimum run-in lubrication for new machine parts.

## **SLOW-MOVING PARTS:**

Ordinary lubricants fail to achieve a hydrodynamic film between slow moving parts under high load. Omega 646 will separate such surfaces even at rest and its low coefficient of friction prevents chatter and stick-slip operation.

## **PREVENTS METAL-TO-METAL**

### **CONTACT:**

Omega 646 absolutely prevents any metal-to-metal contact in the absence of hydrodynamic film. Under load, the micronized platelets present in Omega 646's moly, slide easily upon one another to prevent metal contact. No other conventional lubricant can do so. Omega 646's specialized moly will keep lubricating up to an approximately limit of 750°F (400°C). Therefore Omega 646 can be used in the most demanding, tough and high temperature chains without breakdown or deterioration.

## PREVENTING FRETTING CORROSION:

In limited motion machinery, vibration prevents the forming of hydro-dynamic lubricant film between parts. Conventional lubricants literally vibrate off or migrate away. Omega 646's moly remains in place, reducing metal-to-metal contact and fretting corrosion.

## ANTI-FRICTION BEARINGS:

When bearings overheat, ordinary grease components thin out excessively. Omega 646's moly will continue to protect such surfaces.

## SUPERIOR FOR CHAIN LUBRICATION

Omega 646 is formulated from the ground up with expensive, high-performance constituents. The base suspension lubricant is a high quality, refined paraffinic which displays superior lubrication action and anti-oxidation qualities.

Special viscosity improvers give Omega 646 a stability to temperature fluctuations for lubrication superior to all conventional chain lubricants. It will markedly improve chain lubricity and lower drag on all machinery components dramatically to save operating costs.

## APPLICATION:

Omega 646 can be applied directly onto chains and machine parts by either dipping, using a brush or bath or by drip feed. Any fling-off that may be encountered in certain high-speed chains immediately after application can be ignored as the moly in Omega 646 will hold tenaciously onto the applied surfaces where lubrication is most critical. Omega 646 is used for superior lubrication of all types of chains -conveyors, gear drives, pulleys, etc. and will withstand the punishing high temperature conditions found in dryers and stenters.

## TYPICAL DATA:

TEST	ASTM TEST METHOD	TEST RESULT		
		SAE 40	SAE 50	SAE 90
ISO Viscosity Grade	D-2422	68	150	220
Appearance	Visual	Black Opaque, Tacky		
Density, Kg/L @ 15°C	D-1298	0.875	0.890	0.893
Viscosity, cSt @ 40°C	D-445	76	150	220
Viscosity, cSt @ 100°C	D-445	14.0	19.1	21.3
Viscosity Index	D-2270	191	183	115
Flash Point, COC, °C(°F)	D-92	204(399)	218(424)	264(507)
Pour Point °C(°F)	D-97	-30(-22)	-25(-13)	-22(-8)
Total Base Number, mg KOH/g	D-2896	11.6	11.6	8.2
Foaming Characteristics -				
All Sequences, After Settling	D-892	Nil	Nil	Nil
Rust-Preventing Characteristics, 48 hours saltwater	D-665	Pass	Pass	Pass
Molybdenum Disulphide, % Mass*	Gravimetric	1.0	1.0	1.0

\* MoS<sub>2</sub> contribution 0.9

# SAFETY DATA SHEET



Product name: Omega 646  
Supersedes date: 2015-11-17  
Product No.:

Page: 1/7  
Last revised date: 2018-09-07  
SDS-ID: GB-EN/6.1

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product name: Omega 646  
Container size: 5 l, 20 l

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Application: Engine oil. / Chain oil.

### 1.3. Details of the supplier of the safety data sheet

Supplier: EU importer:

.  
.

Manufacturer ITW PP & F Korea Limited.  
13th Fl., Unit B, PAX Tower  
609 Eonju-ro, Gangnam-gu  
Seoul, Korea 06108  
Tel:+82-2-2088-3560  
Fax:+82-2-513-3567  
[www.magnagroup.com](http://www.magnagroup.com)

### 1.4. Emergency telephone number

Emergency telephone: Call a Poison Center, emergency number or doctor/physician.

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

The product is not classified.

### 2.2. Label elements

The substance/mixture does not meet the criteria for classification and labelling.

### 2.3. Other hazards

Other: Prolonged or repeated contact with skin may cause redness, itching, irritation, eczema, skin cracking and oil acne. Degreasing to skin. The harmful effects may increase in used oil.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

The product contains: mineral oil (DMSO<3% (IP 346)) and additives.  
No classified ingredients, or those having occupational exposure limits, present above the levels of disclosure.

# SAFETY DATA SHEET

Product name:	Omega646	Page:	2/7
Supersedes date:	2015-11-17	Last revised date:	2018-09-07
Product No.:		SDS-ID:	GB-EN/6.1

---

## SECTION 4: FIRST AID MEASURES

### **4.1. Description of first aid measures**

Inhalation: Move into fresh air and keep at rest. In case of persistent throat irritation or coughing: Seek medical attention and bring these instructions.

Skin contact: Remove contaminated clothing immediately and wash skin with soap and water. In case of rashes, wounds or other skin disorders: Seek medical attention and bring along these instructions.

Eye contact: Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Seek medical attention and bring along these instructions.

Ingestion: Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable seek hospital and bring these instructions.

### **4.2. Most important symptoms and effects, both acute and delayed**

Symptoms/effects: See section 11 for more detailed information on health effects and symptoms.

### **4.3. Indication of any immediate medical attention and special treatment needed**

Medical attention/treatments: Treat symptomatically.

## SECTION 5: FIREFIGHTING MEASURES

### **5.1. Extinguishing media**

Extinguishing media: Small fires: Extinguish with carbon dioxide or dry powder.  
Larger fires: Extinguish with foam, carbon dioxide or dry powder.  
Do not use water jet as an extinguisher, as this will spread the fire.

### **5.2. Special hazards arising from the substance or mixture**

Specific hazards: During fire, gases hazardous to health may be formed.

### **5.3. Advice for firefighters**

Protective equipment for fire-fighters: Selection of respiratory protection for fire fighting: follow the general fire precautions indicated in the workplace.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### **6.1. Personal precautions, protective equipment and emergency procedures**

Personal precautions: Avoid inhalation of oil mist and contact with skin and eyes. Follow precautions for safe handling described in this safety data sheet.

### **6.2. Environmental precautions**

Environmental precautions: Do not discharge into drains, water courses or onto the ground.

### **6.3. Methods and material for containment and cleaning up**

Methods for cleaning up: Absorb spillage with oil-absorbing material. Clean contaminated area with oil-removing material.

### **6.4. Reference to other sections**

References: For personal protection, see section 8.  
For waste disposal, see section 13.

---

# SAFETY DATA SHEET

Product name:	Omega646	Page:	3/7
Supersedes date:	2015-11-17	Last revised date:	2018-09-07
Product No.:		SDS-ID:	GB-EN/6.1

---

## SECTION 7: HANDLING AND STORAGE

### **7.1. Precautions for safe handling**

Safe handling advice: Observe good chemical hygiene practices. Avoid prolonged and repeated contact with oil, particularly used oil. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags moistened with oil into pockets.

Technical measures: Use work methods which minimise oil mist production.

Technical precautions: When working with heated oil, mechanical ventilation may be required.

### **7.2. Conditions for safe storage, including any incompatibilities**

Technical measures for safe storage: No special precautions.

Storage conditions: Store in tightly closed original container.

### **7.3. Specific end use(s)**

Specific use(s): Lubricant.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### **8.1. Control parameters**

No occupational exposure limit assigned.

### **8.2. Exposure controls**

Engineering measures: Provide adequate ventilation and minimise the risk of inhalation of vapours and oil mist. Provide access to washing facilities incl. soap, skin cleanser and fatty cream.

Personal protection: Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Respiratory equipment: In case of inadequate ventilation or risk of inhalation of oil mist, suitable respiratory equipment with combination filter (type A2/P3) can be used.

Hand protection: Wear protective gloves. Nitrile gloves are recommended, but be aware that the liquid may penetrate the gloves. Frequent change is advisable. Other types of gloves can be recommended by the glove supplier.

Eye protection: Risk of contact: Wear goggles/face shield.

Hygiene measures: Wash hands after handling. Wash contaminated clothing before reuse.

Environmental Exposure Controls: Not available.

---

# SAFETY DATA SHEET

Product name: Omega646  
Supersedes date: 2015-11-17  
Product No.:

Page: 4/7  
Last revised date: 2018-09-07  
SDS-ID: GB-EN/6.1

---

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance: Liquid.  
Colour: Black.  
Odour: Almost odourless.  
pH: Not relevant.  
Melting point / freezing point: Not available.  
Boiling point: Not available.  
Flash point: > 150 °C  
Evaporation rate: Not available.  
Flammability (solid, gas): Not applicable.  
Explosive limits Not available.  
Vapour pressure: Not available.  
Vapour density: Not available.  
Relative density: ~0.9  
Solubility: Insoluble in water.  
Partition coefficient (n-octanol/water): Not available.  
Auto-ignition temperature (°C): Not available.  
Decomposition temperature (°C): Not available.  
Viscosity: 68 / 150 / 220 mm<sup>2</sup>/s (40°C)

### 9.2. Other information

Other data: Not available.

---

# SAFETY DATA SHEET

Product name: Omega646  
Supersedes date: 2015-11-17  
Product No.:

Page: 5/7  
Last revised date: 2018-09-07  
SDS-ID: GB-EN/6.1

---

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

Reactivity: Not reactive.

### 10.2. Chemical stability

Stability: Stable under normal temperature conditions.

### 10.3. Possibility of hazardous reactions

Hazardous Reactions: None known.

### 10.4. Conditions to avoid

Conditions to avoid Heat, sparks, flames.

### 10.5. Incompatible materials

Incompatible materials: Strong oxidising substances.

### 10.6. Hazardous decomposition products

Hazardous decomposition products: None in particular.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

The harmful effects may increase in used oil.

Inhalation: Inhalation of oil mist or vapours formed during heating of the product will irritate the respiratory system and provoke coughing.

Skin contact: Degreasing. Prolonged or frequent contact may cause redness, itching, irritation, eczema, skin cracking and oil acne.

Eye contact: Splashes may irritate.

Ingestion: May irritate and cause malaise.

Specific effects: Prolonged or repeated contact with used oil may cause serious skin diseases, such as dermatitis and skin cancer.

---

# SAFETY DATA SHEET

Product name:	Omega646	Page:	6/7
Supersedes date:	2015-11-17	Last revised date:	2018-09-07
Product No.:		SDS-ID:	GB-EN/6.1

---

## SECTION 12: ECOLOGICAL INFORMATION

### **12.1. Toxicity**

Ecotoxicity: Oil spills are generally hazardous to the environment.

### **12.2. Persistence and degradability**

Degradability: The product is expected to be slowly biodegradable.

### **12.3. Bioaccumulative potential**

Bioaccumulative potential: No data available on bioaccumulation.

### **12.4. Mobility in soil**

Mobility: No data available.

### **12.5. Results of PBT and vPvB assessment**

PBT/vPvB: No data available.

### **12.6. Other adverse effects**

Other adverse effects: None known.

## SECTION 13: DISPOSAL CONSIDERATIONS

### **13.1. Waste treatment methods**

Dispose of waste and residues in accordance with local authority requirements. Waste is classified as hazardous waste.

Waste from residues: EWC-code: 13 02 05

## SECTION 14: TRANSPORT INFORMATION

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

### **14.1. UN number**

UN-No: -

### **14.2. UN proper shipping name**

Proper Shipping Name: -

### **14.3. Transport hazard class(es)**

Class: -

### **14.4. Packing group**

PG: -

### **14.5. Environmental hazards**

Marine pollutant: -

Environmentally Hazardous substance: -

### **14.6. Special precautions for user**

Special precautions: -

### **14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code**

Transport in bulk: -

---



# SAFETY DATA SHEET

Product name:	Omega646	Page:	7/7
Supersedes date:	2015-11-17	Last revised date:	2018-09-07
Product No.:		SDS-ID:	GB-EN/6.1

---

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulation: Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.  
Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, with amendments.  
The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments.  
EH40/2005, Workplace exposure limits 2005, with amendments.  
The List of Wastes (England) (Amendment) Regulations 2005. (SI 2005 No. 895).

### 15.2. Chemical Safety Assessment

CSA status: No information available.

## SECTION 16: OTHER INFORMATION

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

Handling of used oils:

Protect health - avoid prolonged and repeated skin contact. Wash with soap and water. Protect the environment - do not pollute drains, water courses or the soil. Contact your local authority for any used oil disposal instructions.

The following sections contain revisions or new statements: 1

Omega Manufacturing Division  
13th floor, Unit B, PAX Tower, 609 Eonju-ro,  
Gangnam-Gu, Seoul, Korea 06108  
Tel : +82-2-2088-3560  
Fax : +82-2-513-3567  
Web site : [www.magnagroup.com](http://www.magnagroup.com)

The Omega Trade Mark is the property of ITW, Inc., and is used under license by ITW PP & F Korea Limited.

---

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.

Made by DHI - Environment and Toxicology, Agern Allé 5, DK-2970 Hørsholm, Denmark.  
[www.dhigroup.com](http://www.dhigroup.com)

---