

DESCRIPTION:

New formulation Omega 95 is the latest generation of Omega's premier severe saltwater-and corrosive atmosphere-resistant grease. It is characterized by an extremely high load carrying capability, superior resistance to water, unparalleled mechanical stability, enhanced resistance to oxidation and corrosion and exemplary performance in high temperature applications. Omega 95 will continue to lubricate under complete immersion or high water washout applications that no ordinary grease can endure.

ENHANCED CAPABILITIES:

New and improved Omega 95 now provides still higher water wash resistance and immersed lubrication performance from its high density characteristics. Not only is improved Omega 95 extremely capable at higher temperatures, it will also perform superbly even at lower temperatures as low as -23°C (or - 10°F) or near-arctic conditions!!! Omega 95 also contains absolutely no heavy metals, harmful or environmentally undesirable additives which makes this lubricant suitable for the lubrication of reservoir sluice gates and mechanisms, for freshwater lake and canal equipment, etc.

Due to the enhanced purity performance with this all-new Omega 95 formulation, the traditional applications of lubricating shipboard equipment and dockside equipment -including dry-dock and ship repair/building equipment can be expanded to include steam cleaning equipment used in bottling plants, abattoirs, etc., where wet conditions are combined with high heat and pressurized water wash.

Omega 95 works perfectly in anti-friction bearings, both low and high speed ordinary bearings, for lubricating conveyors and for a large variety of construction, irrigation and agricultural equipment lubrication, where wet conditions are often encountered.

Due to Omega 95's improved stay-put qualities, it will readily withstand the vigorous and often difficult shock loading and high heat encountered in mining where underground water and slush tends to inundate and saturate the equipment. In addition to being the best grease for protection of waterside equipment, Omega 95 now provides its exemplary corrosion resistance to a wider variety of applications.



Copyright, All rights reserved. ITW PP & F Korea Limited reserves the right to modify or change this product for purposes of improving its performance characteristics.

OPIM95-1	Ver. 2.0	Rev. 3.0
Rev. Date: 2 Jan 2019		
Reference: CKL		

TYPICAL DATA:

TEST	ASTM TEST METHOD	TEST RESULT
Base Oil		
Viscosity, cSt at 40°C	D-445	221
Flash Point, °C	D-92	249
Pour Point, °C	D-97	-9
Dropping Point, °C	D-2265	318
Worked Penetration	D-217	
60 strokes		282
Worked 100,000 strokes, % change		2.3
Worked 10,000 strokes, with 50/50 water, % change		8.0
Timken OK Load, Lbs	D-2509	60
Four Ball, EP	·	
Weld Point, Kg	D-2596	500
Load Wear Index (LWI)	D-2596	65
Four Ball Wear, mm	D-2266	0.39
Rust Prevention Rating	D-1743	1, 1, 1
Water Washout @ 175°F (79.4°C), %	D-1264	1.0
Salt Fog Corrosion, 1 mil d.f.t., hours	B-117	>300
Resistance to Water Spray, % retained	D-4049	80
Wheel Bearing Leakage, gm	D-1263	0.5
Roll Stability, % Change	D-1831	5
Oil Separation, Wt. %	D-1742	0.2
NLGI Grade	-	#2
Operating Temperature Range,°C	-	-23 to 200
Color	-	Tan





SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE			
Product No.:		SDS-ID:	GB-EN/4.0
Supersedes date: 201	19-05-09	Last revised date:	2022-12-20
	nega 95 - Super Corrosion-Control Grease GI #2	Page:	1/12

COMPANY/UNDERTAKING

1.1. Product identifier			
Product name:	Omega 95 - Super Corrosion-	-Control Grease NLGI #2	
<u>UFI:</u>	6480-E086-Y00C-WPV4		
Container size:	Not available.		
1.2. Relevant identified uses	of the substance or mixture and	l uses advised against	
Application:	Grease.		
1.3. Details of the supplier of	the safety data sheet		
Supplier:	GB importer:	Sovereign Lubricants (UK) Ltd, Crowtrees Lane,	
<u>Manufacturer:</u>	ITW PP & F Korea Limited 13th Fl., Unit B, PAX Tower 609 Eonju-ro, Gangnam-Gu Seoul, Korea 06108 Tel:+82-2-2088-3560 Fax:+82-2-513-3567 magna@magnagroup.com www.magnagroup.com	Rastrick, West Yorkshire, HD6 3LZ T:01484 718674 - F: 01484 400164 enquiries@sovereign-omega.co.uk www.sovereign-omega.co.uk	
1.4. Emergency telephone number			

NHS: 111 Emergency telephone:

Product name:	Omega 95 - Super Corrosion-Control Grease NLGI #2	Page:	2/12
Supersedes date:	2019-05-09	Last revised date:	2022-12-20
Product No.:		SDS-ID:	GB-EN/4.0

SECTION 2: HAZARDS ID	SECTION 2: HAZARDS IDENTIFICATION		
2.1. Classification of the substance or mixture			
<u>CLP:</u>	Eye Irrit. 2;H319		
2.2. Label elements			
	\wedge		
	Warning		
	warning		
H319	Causes serious eye irritation.		
P280	Wear eye protection.		
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact		
	lenses, if present and easy to do. Continue rinsing.		
P337 + P313	If eye irritation persists: Get medical advice/attention.		
DE04			
P501	Dispose of contents/container as hazardous waste.		
	Contains Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts and Sulfonic acids, petroleum, calcium salts. May produce an allergic reaction.		
2.3. Other hazards			
<u>PBT/vPvB:</u>	This product does not contain any PBT or vPvB substances.		
<u>Other:</u>	Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping. The harmful effects may increase in used grease.		

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Only classified substances above threshold limits or substances with an exposure limit are shown. All substances in the product are either registered or exempt from registration under REACH.

Produc	t name:		Omega 95 - Super Co NLGI #2	orrosion-Control Grease	Page:	3/12	
Supers	edes date:		2019-05-09		Last revised date:	2022-12-20	
Produc	t No.:				SDS-ID:	GB-EN/4.0	
CLP:							
<u>%:</u>	CAS-No.:	<u>EC No.:</u>	REACH Reg. No:	Chemical name:	Hazard classification:	Notes:	
1 - <5	68584-23-6	271-529-4	01-2119492627-25- 0000 -XXXX	Benzenesulfonic acid, C10- 16-alkyl derivs., calcium salts	Skin Sens. 1B;H317	SCL	
1 - <5	61789-86-4	263-093-9	01-2119488992-18- 0000 -XXXX	Sulfonic acids, petroleum, calcium salts	Skin Sens. 1B;H317	SCL	
1 - <3	26264-06-2	247-557-8	01-2120122335-68- 0000 -XXXX	Calcium dodecylbenzenesulphonate	Acute Tox. 4;H302 Skin Irrit. 2;H315 Eye Dam. 1;H318 Aquatic Chronic 4;H413		
<u>Chem</u>	ical name:			<u>SCL</u>			
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts		Skin Sens. 1B;H317: C	Skin Sens. 1B;H317: C ≥ 10%				
Sulfoni	c acids, petrole	eum, calcium	salts	Skin Sens. 1B;H317: C	Skin Sens. 1B;H317: C ≥ 10%		
Calcium dodecylbenzenesulphonate							
Notes	:						
				SCL = Specific Cond	centration Limit.		
References:		The full text for all has section 16.	azard statements is disp	layed in			

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures		
Inhalation:	Move into fresh air and keep at rest. In case of persistent throat irritation or coughing: Seek medical attention and bring these instructions.	
<u>Skin contact:</u>	Remove contaminated clothing immediately and wash skin with soap and water. In case of rashes, wounds or other skin disorders: Seek medical attention and bring along these instructions.	
Eye contact:	Do not rub eye. Immediately rinse with water. Make sure to remove any contact lenses from the eyes before rinsing. Continue to rinse for at least 15 minutes and get medical attention.	
Ingestion:	Immediately rinse mouth and drink 1-2 glasses of water. Keep person under observation. If uncomfortable: Transportation to hospital. Bring along these instructions.	
4.2. Most important symptom	s and effects, both acute and delayed	
Symptoms/effects:	See section 11 for more detailed information on health effects and symptoms.	

4.3. Indication of any immediate medical attention and special treatment needed

<u>Medical attention/treatments:</u> Treat symptomatically.

Product name:	Omega 95 - Super Corrosion-Control Grease NLGI #2	Page:	4/12
Supersedes date:	2019-05-09	Last revised date:	2022-12-20
Product No.:		SDS-ID:	GB-EN/4.0

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media:	Small fires: Extinguish with carbon dioxide or dry powder.
	Larger fires: Extinguish with foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

<u>Specific hazards:</u> During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Protective equipment for fire-
fighters:Selection of respiratory protection for fire fighting: follow the general fire
precautions indicated in the workplace.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

<u>Personal precautions:</u> Avoid contact with skin and eyes. Follow precautions for safe handling described in this safety data sheet.

6.2. Environmental precautions

Environmental Do not discharge into drains, water courses or onto the ground.

precautions:

6.3. Methods and material for containment and cleaning up

<u>Methods for cleaning up:</u> Absorb spillage with oil-absorbing material. Clean contaminated area with oilremoving material.

6.4. Reference to other sections

References:

For personal protection, see section 8. For waste disposal, see section 13.

Product name:	Omega 95 - Super Corrosion-Control Grease NLGI #2	Page:	5/12
Supersedes date:	2019-05-09	Last revised date:	2022-12-20
Product No.:		SDS-ID:	GB-EN/4.0

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Safe handling advice:	Observe good chemical hygiene practices. Avoid prolonged and repeated contact with grease, particularly used grease. Always remove grease with soap and water or skin cleaning agent, never use organic solvents.
Technical measures:	Work practice should minimise contact.
Technical precautions:	When working with heated grease, mechanical ventilation may be required.
7.2. Conditions for safe storage	ge, including any incompatibilities
<u>Technical measures for safe</u> storage:	No special precautions.
Storage conditions:	Store in tightly closed original container in a dry, cool and well-ventilated place.
7.3. Specific end use(s)	
<u>Specific use(s):</u>	Not relevant.

Product name:	Omega 95 - Super Corrosion-Control Grease NLGI #2	Page:	6/12
Supersedes date:	2019-05-09	Last revised date:	2022-12-20
Product No.:		SDS-ID:	GB-EN/4.0

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

No occupational exposure limit assigned.

8.2. Exposure controls

Engineering measures:	Provide adequate ventilation. When working with heated grease, mechanical ventilation may be required. Provide access to washing facilities incl. soap, skin cleanser and fatty cream.
Personal protection:	Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.
Respiratory equipment:	In case of inadequate ventilation use suitable respirator. Use respiratory equipment with particle filter, type P2.
Hand protection:	Risk of contact: Wear protective gloves. Nitrile gloves are recommended. Breakthrough time: > 4h; Thickness: > 0.3 mm Other types of gloves can be recommended by the glove supplier.
Eye protection:	Wear goggles/face shield.
Skin protection:	Wear apron or protective clothing in case of contact.
Hygiene measures:	Wash hands after handling.
Environmental Exposure Controls:	Not available.

Product name:	Omega 95 - Super Corrosion-Control Grease NLGI #2	Page:	7/12
Supersedes date:	2019-05-09	Last revised date:	2022-12-20
Product No.:		SDS-ID:	GB-EN/4.0

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state:	Paste.
<u>Colour:</u>	Tan.
<u>Odour:</u>	Mild. Hydrocarbon.
<u>pH:</u>	not relevant
Melting point / freezing point:	not available
Boiling point:	not available
Flash point:	> 180 °C
Evaporation rate:	Not relevant.
Flammability (solid, gas):	Not relevant.
Explosive limits	not available
Vapour pressure:	<0.0008 hPa @ 20 °C
Vapour density:	Not available.
Relative density:	0.95 - 1.05 (25 °C)
<u>Solubility:</u>	insoluble in water
Partition coefficient (n- octanol/water):	Not available.
<u>Auto-ignition</u> temperature (°C):	Not available.
Decomposition temperature (°C):	not available
<u>Viscosity:</u>	Not applicable.
Explosive properties:	Non-explosive
Oxidising properties:	Non-oxidising
9.2. Other information	
<u>Other data:</u>	Not relevant.

Product name:	Omega 95 - Super Corrosion-Control Grease NLGI #2	Page:	8/12
Supersedes date:	2019-05-09	Last revised date:	2022-12-20
Product No.:		SDS-ID:	GB-EN/4.0
SECTION 10: STABILITY	AND REACTIVITY		
10.1. Reactivity			
Reactivity:	Not reactive.		
10.2. Chemical stability			
Stability:	Stable under normal temperature conditions.		
10.3. Possibility of hazardous	reactions		
Hazardous Reactions:	None known.		
10.4. Conditions to avoid			
Conditions to avoid	Water, moisture.		
10.5. Incompatible materials			
Incompatible materials:	Strong oxidising substances.		
<u>P</u>			
10.6. Hazardous decomposit	on products		
Hazardous decomposition	None in particular.		
products:			

Product name:	Omega 95 - Super Corrosion-Control Grease NLGI #2	Page:	9/12
Supersedes date:	2019-05-09	Last revised date:	2022-12-20
Product No.:		SDS-ID:	GB-EN/4.0

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

The harmful effects may increase in used grease.

The narmul ellects may incre	
Acute Toxicity (Oral):	Based on available data, the classification criteria are not met.
Acute Toxicity (Dermal):	Based on available data, the classification criteria are not met.
Acute Toxicity (Inhalation):	Based on available data, the classification criteria are not met.
Skin Corrosion/Irritation:	Based on available data, the classification criteria are not met.
Serious eye damage/irritation	: Causes serious eye irritation.
<u>Respiratory or skin</u> sensitisation:	Based on available data, the classification criteria are not met.
Germ cell mutagenicity:	Based on available data, the classification criteria are not met.
Carcinogenicity:	Based on available data, the classification criteria are not met.
Reproductive Toxicity:	Based on available data, the classification criteria are not met.
STOT - Single exposure:	Based on available data, the classification criteria are not met.
STOT - Repeated exposure:	Based on available data, the classification criteria are not met.
Aspiration hazard:	Based on available data, the classification criteria are not met.
Inhalation:	Inhalation of oil mist or vapours formed during heating of the product will irritate the respiratory system and provoke coughing.
<u>Skin contact:</u>	Degreasing. Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping. May cause sensitisation by skin contact.
Eye contact:	Risk of serious damage to eyes.
Ingestion:	May irritate and cause malaise.
Specific effects:	Prolonged or repeated contact with used grease may cause serious skin diseases, such as dermatitis. May cause allergic skin disorders in sensitive individuals.
Toxicological data:	ATE (Oral): >2000 mg/kg (calculated) ATE (Dermal): >2000 mg/kg (calculated)
11.2. Information on other ha	zards

11.2. Information on other hazards

Endocrine disrupting	The product does not contain any substance identified as having endocrine
properties:	disrupting properties.

Product name:	Omega 95 - Super Corrosion-Control Grease NLGI #2	Page:	10/12
Supersedes date:	2019-05-09	Last revised date:	2022-12-20
Product No.:		SDS-ID:	GB-EN/4.0

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity	
<u>Ecotoxicity:</u>	The product contains a substance which may cause long term adverse effects in the aquatic environment. Calcium dodecylbenzenesulphonate LC50 (Fish, Cyprinus carpio (48 h): 2.8 - 4.2 mg/l EC50 (Daphnia magna, 48 hours): 2.9 mg/l EC50 (Algae, Scenedesmus capricornutum, 96 H): 29 mg/l NOEC (Water flea, 21 days): 1.18 mg/l Greases are generally hazardous to the environment.
12.2. Persistence and degrad	dability
-	No data available.
<u>Degradability:</u>	
12.3. Bioaccumulative poten	tial
Bioaccumulative potential:	No data available on bioaccumulation.
<u>12.4. Mobility in soil</u>	
<u>Mobility:</u>	No data available. The product is insoluble in water and will spread on the water surface.
	The product is insoluble in water and will spread on the water surface.
12.5. Results of PBT and vP	vB assessment
<u>PBT/vPvB:</u>	This product does not contain any PBT or vPvB substances.
12.6. Endocrine disrupting pl	
Endocrine disrupting properties:	The product does not contain any substance identified as having endocrine disrupting properties.
12.7. Other adverse effects	
Other adverse effects:	None known.
SECTION 13: DISPOSAL	CONSIDERATIONS
13.1. Waste treatment metho	<u>ods</u>
Dispose of waste and residu hazardous waste.	es in accordance with local authority requirements. Waste is classified as
Waste from residues:	EWC-code: 20 01 26
Contaminated packaging:	Dispose of contaminated packings as residue.

Product name:	Omega 95 - Super Corrosion-Control Grease NLGI #2	Page:	11/12
Supersedes date:	2019-05-09	Last revised date:	2022-12-20
Product No.:		SDS-ID:	GB-EN/4.0

SECTION 14: TRANSPORT INFORMATION

_

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/AND/RID).

14.1. UN number

UN-No:

14.2. UN proper shipping name

Proper Shipping Name:

14.3. Transport hazard class(es)

Class:

14.4. Packing group

<u>PG:</u>

14.5. Environmental hazards

Marine pollutant:

<u>Environmentally Hazardous</u> - <u>substance:</u>

14.6. Special precautions for user

Special precautions:

. ...

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

. .

. ..

-

_

Transport in bulk:

-

SECTION 15: REGULATORY INFORMATION

. .

15.1. Safety, health and e	environmental regulations/legislation specific for the substance or mixture
National regulation:	UK Statutory Instruments, 2021 No. 904, CONSUMER PROTECTION ENVIRONMENTAL PROTECTION HEALTH AND SAFETY. The REACH etc. (Amendment) Regulations 2021.
	Statutory Instruments 2008 No. 2852 - The REACH Enforcement Regulations 2008.
	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments.
	European Union (Withdrawal) Act 2018, as amended. EH40/2005, Workplace exposure limits 2005, with amendments. The List of Wastes (England) (Amendment) Regulations 2005. (SI 2005 No. 895).

. . ..

...

15.2. Chemical Safety Assessment

CSA status:

Not relevant.

Product name:	Omega 95 - Super Corrosion-Control Grease NLGI #2	Page:	12/12
Supersedes date:	2019-05-09	Last revised date:	2022-12-20
Product No.:		SDS-ID:	GB-EN/4.0

SECTION 16: OTHER INFORMATION

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions. Handling of used oils:

Protect health - avoid prolonged and repeated skin contact. Wash with soap and water. Protect the environment - do not pollute drains, water courses or the soil. Contact your local authority for any used oil disposal instructions.

The following sections contain revisions or new statements: 1, 2, 3, 4, 7, 8, 9, 10, 11, 12, 13, 15, 16.

Omega Manufacturing Division 13th floor, Unit B, PAX Tower, 609 Eonju-ro, Gangnam-Gu, Seoul, Korea 06108 Tel : +82-2-2088-3560 Fax : +82-2-513-3567 Web site : www.magnagroup.com

The Omega Trade Mark is the property of ITW, Inc., and is used under license by ITW PP & F Korea Limited.

<u>Abbreviations and acronyms</u> used in the safety data sheet:	ATE = Acute Toxicity Estimate. CSA= Chemical Safety Assessment. EC50 = Effective Concentration 50%. LC50 = Lethal Concentration 50%. NOEC = No Observed Effect Concentration. PBT = Persistent, Bioaccumulative and Toxic. SCL = Specific Concentration Limit. vPvB = very Persistent and very Bioaccumulative.	
Additional information:	Classification according to Regulation (EC) No. 1272/2008: Calculation method.	
Wording of H-statements:		
H302	Harmful if swallowed.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H413	May cause long lasting harmful effects to aquatic life.	

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.

Made by DHI - Environment and Toxicology, Agern Allé 5, DK-2970 Hørsholm, Denmark. www.dhigroup.com.